

Certified compliance ... The proof

Reception

Save time and buy in complete confidence by selecting furniture conforming to current regulations and standards.

Supported by tests, the **NF Collectivité** mark (furniture for public spaces) provides you with objective proof that the product complies with specified requirements and takes into account the appropriate criteria for this specific use in terms of:

- > **Safety** > **Robustness**
- > **Durability** > **Hygiene**

For you, it is also the assurance that the manufacturer knows how to ensure a constant level of quality for all furniture marked **NF Collectivité**.

CABINETS

> Safety

Stability when loaded drawers and doors are opened

> Strength

Load on pull-out shelves at 1 kg/dm²

10 shocks on pull-out shelf catches with a weight of 1.7 kg

Load on top at 1.5 kg/dm²

Drawer loading at 0.5 kg/dm³ and 0.7 kg/dm³

Loads on hanging rails at 40 kg/metre length

4 accidental drops from a height of 100 mm

> Durability

Doors opened 40,000 times

Loaded drawers opened 50,000 times

1000 lateral thrusts of 300 N testing rigidity

ARMCHAIR AND LOW FIRESIDE CHAIR

> Safety

Rearward, side and forward stability

Fire resistance

> Strength

Load on the seat base of 1500 kg

Horizontal thrust of 700 N on the seat back

Vertical thrust of 700 N on the seat back

Thrust of 700 N on the armrests

Drop of a weight of 90 kg onto the seat base

Drop of a weight of 125 kg onto the seat base

3 accidental drops from a height of 100 mm and

one from 300 mm

> Durability

75 kg weight dropped 40,000 times

30,000 thrusts of 400 N on the seat back

40,000 thrusts of 400 N on the armrests

Seat loaded with 75 kg tipped forwards and

rearwards 12,000 times

Seat loaded with 40 kg tipped 6000 times on its

side



TABLE

> Safety

Stability

> Strength

Load on the top of 75 or 100 kg

5 accidental drops of the table by tipping it over

> Durability

10,000 lateral thrusts of 300 N testing rigidity

5000 torsional thrusts of 200 N for tables with a central leg

5000 vertical thrusts of 750 N for tables with unobstructed sides or central leg

70,000 rolling operations for loaded rolling tables

2000 operations for folding tables